



Material Safety Data Sheet

PRODUCTO™ CB-101

PARTS CLEANER CONCENTRATE

DATE EFFECTIVE: 06-10-2010

1 CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Manufacturer: CIMCOOL® Industrial Products LLC
3000 Disney Street
Cincinnati, OH 45209 United States

Emergency: Telephone (USA): 1-800-424-9300 (CHEMTREC)
Telephone (Outside USA): 1-703-527-3887 (CHEMTREC)

General Information: Telephone: 1-513-458-8199

Generic Name: Water Soluble Parts Cleaner Concentrate

2 EMERGENCY INFORMATION

Product is strongly alkaline. Product is corrosive to skin, eyes and aluminum. Highway spills could result in slippery conditions. No other significant health effects are associated with this material. Contact may result in irreversible tissue damage.

3 POTENTIAL HEALTH EFFECTS OF DIRECT EXPOSURE

	Product	Product at Use Dilution
Inhalation:	Not Applicable	Extended exposure to mist may cause upper respiratory irritation.
Eye Contact:	Product is corrosive to eyes.	Product at use dilution may be a primary eye irritant.
Skin Contact:	Product is corrosive to skin.	May be corrosive to skin.
Ingestion:	May be harmful if swallowed.	Swallowing small quantities may cause diarrhea, nausea or vomiting. Digestive tract damage may occur.

Medical Conditions generally aggravated by exposure

May aggravate existing skin irritation where further defatting or skin penetration could occur.

Skin irritation (redness and dryness of hands) may be experienced when the diluted product has been contaminated by certain oils, by dissolved metals, or when mix ratio is too strong. When problems occur, use of water-resistant barrier creams may be a temporary control measure. Contact CIMCOOL® Industrial Products LLC Technical Services at 1-513-458-8199 for specific recommendations.

When used in applications generating high levels of mist, operator exposure can be minimized by proper ventilation, use of mist collectors or splash guards, as appropriate. If there is doubt about actual mist levels present, monitoring should be conducted.

Carcinogen Listings: NTP: No IARC: No OSHA: No

Signs and symptoms of exposure

Acute

Eye injury may result from contact with product. Skin irritation can result from improper use and handling of product.

4 EMERGENCY AND FIRST AID PROCEDURES

Eyes

In case of eye contact, flush immediately with running water for at least 15 minutes, and get prompt medical attention.

Skin Contact

For skin contact flush with large amounts of water while removing contaminated clothing. Remove contaminated shoes and clothing and launder before reuse. If irritation persists, get medical attention.

Diluted product is not irritating to the skin when used as recommended and good personal hygiene is practiced.

Ingestion

Dilute by drinking water followed by fruit juice or vinegar. If the material is swallowed, DO NOT INDUCE VOMITING. Immediately contact a physician and obtain treatment. Swallowing small quantities of diluted product may cause nausea, diarrhea or abdominal distress.

Inhalation

Inhalation can occur in applications where high mist levels are generated. OSHA has set a PEL of 15 mg/m³ for any airborne particulate as a nuisance level of exposure. NIOSH has set a REL of 0.5 mg/m³ for metalworking fluid mist. If symptoms persist, get medical attention.

5 CONTROL MEASURES

Respiratory protection

Product is not volatile.

In metalworking fluid applications where time-weighted exposures are 0.5 to 5 mg/m³, mist reduction through improved ventilation or process modification is recommended by NIOSH. Where this is not possible, NIOSH recommends the use of any air purifying, half-mask respirator including a disposable respirator, equipped with any P- or R-series particulate filter. If the average exposure will exceed 5 mg/m³, NIOSH recommends use of a powered, air-purifying respirator equipped with a hood or helmet and a HEPA filter. If respiratory problems are present when mist levels are < 0.5 mg/m³, respiratory protection should be based on the individual recommendation of a qualified health care provider.

Caution

The appropriate use and type of respirator is dependent upon use of the product and local operating conditions.

Ventilation

For most applications, adequate shop ventilation is needed. However, when high mist levels are generated or where machines are close together or ventilation is inadequate, operators may experience respiratory irritation. For such applications, use of splash guards or mist collectors is recommended.

Eye protection

Wear chemical goggles and face shield.

Other protective clothing or equipment

Use effective plant protective clothing as appropriate.

Work / Hygiene Practices

Good personal hygiene should always be followed.

Protective Gloves

Impervious gloves, such as nitrile gloves, are recommended when handling product. Impervious gloves, such as nitrile gloves, are recommended when handling product concentrate.

6 HAZARDOUS INGREDIENTS / IDENTITY INFORMATION

These ingredients may contribute to the acute product hazards listed under the Potential Health Effects section. Other substances, not hazardous under the OSHA Hazard Communication Standard, may be present. Further composition information may be available to health professionals as provided in the Standard.

Component	CAS #	Percent
ETHYLENEDIAMINE-TETRAACETIC ACID, TETRASODIUM SALT	64-02-8	5 - 10
ALCOHOLS, C9-11, ETHOXYLATED	68439-46-3	3 - 7
QUATERNARY AMMONIUM COMPOUNDS, COCO ALKYL BIS(HYDROXYETHYL)METHYL, ETHOXYLATED, CHLORIDES	61791-10-4	1 - 5
ETHOXYLATED COCONUT OIL ALKYL AMINE	61791-14-8	1 - 5

7 FIRE AND EXPLOSION HAZARD DATA

Extinguishing Media

Not Applicable

Hazardous Combustion Products

Smoke, fumes, oxides of nitrogen, and oxides of carbon

Flash Point: Not Applicable

Lower Explosive Limit: Not Applicable

Upper Explosive Limit: Not Applicable

HMIS RATINGS

Health 3

Flammability Classification 0

Reactivity 0

NFPA RATINGS

Health 3

Flammability Classification 0

Reactivity 0

8 ACCIDENTAL RELEASE MEASURES

Contain the spill, collect on absorbent material, and discard as dictated by Federal, state and local regulations that may apply. Flush area thoroughly with water.

Reportable Quantity: None

9 WASTE DISPOSAL

For Used Product

Disposal procedures must comply with local, county, state and Federal regulations. If pre-treatment is needed, ultrafiltration, emulsion breaking or evaporation may be used. Contact CIMCOOL® Industrial Products LLC at 1-513-458-8199 for assistance.

For Unused Product

Product is a hazardous waste as defined under 40 CFR 261. Contact CIMCOOL® Industrial Products LLC at 1-513-458-8199 for assistance.

Empty Containers

Empty containers will contain a residue which is considered a hazardous waste under RCRA regulations.

10 HANDLING AND STORAGE

Avoid contact of product with eyes or skin. Wash thoroughly after handling. Do not swallow. Do not store product concentrate in direct sunlight or elevated temperatures. Use only as recommended by CIMCOOL® Industrial Products LLC . Protect from freezing.

Other Precautions

Contains amines. Do not add sodium nitrite or other nitrosating agents to this product because suspected cancer-causing nitrosamines may be formed.

11 PHYSICAL / CHEMICAL CHARACTERISTICS

Boiling Point:	212 °F (100 °C)
Specific Gravity:	1.07
Evaporation Rate:	Like water when diluted
Solubility (H2O):	100 % Miscible
Volatile Organic Content (by ASTM D2369):	Not determined
pH (Concentrate):	12.7
pH (Mix):	11.5 @ 5.0%
Recommended Starting Dilution:	4.0 - 6.0%
Appearance/Odor:	Clear/Chemical

12 REACTIVITY

Stability

Stable under normal conditions.

Conditions to avoid

Use as directed.

Materials to avoid

Avoid contact with strong acids or oxidizers to product.

Hazardous Polymerization

Will not occur.

Combustion Products

Smoke, fumes, oxides of nitrogen, and oxides of carbon

13 TRANSPORTATION INFORMATION

BY LAND

Hazardous Materials Description and Proper Shipping Name (49 CFR 172.101)

Corrosive liquid, basic, organic, n.o.s. III (contains ethylenediamine-tetraacetic acid, tetrasodium salt)

Hazard Class (49 CFR 172.101): 8

Identification Number: UN3267

Packaging Group: III

BY AIR OR VESSEL

Hazardous Materials Description and Proper Shipping Name (49 CFR 172.101)

Corrosive liquid, basic, organic, n.o.s. III (contains ethylenediamine-tetraacetic acid, tetrasodium salt)

Hazard Class (49 CFR 172.101): 8

Identification Number: UN3267

Packaging Group: III

14 REGULATORY INFORMATION

EXPOSURE GUIDELINES

REGULATED MATERIAL	NIOSH REL	OSHA PEL	OSHA STEL	ACGIH TLV	ACGIH STEL
--------------------	-----------	----------	-----------	-----------	------------

CERCLA

No components of this product are present at levels which require reporting under 40 CFR 302.4.

EPCRA (SARA) TITLE III Extremely Hazardous Substances (302): None

Hazardous Substances (311/312)

Product is a hazardous substance as defined under the OSHA Hazard Communication Standard and may be reportable under the provisions of SARA Sections 311 and 312.

HAZARD CATEGORIES

Acute Health: Yes

Chronic Health: No

Fire: No

Sudden Release of Pressure: No

Reactive: No

RCRA

Product concentrate meets the definition of a hazardous waste as defined under 40 CFR 261.

TSCA

The ingredients of this product are on the TSCA inventory.

State Right to Know

Many states have enacted Community Right-To-Know laws which require information beyond that mandated by federal laws. Since some of these laws are inconsistent with the federal laws, the information in this sheet may not fully meet the requirements of every state.

This product is not subject to California's South Coast Air Quality Management District Rule 1144 (Rule only applicable to Vanishing Oils and Rust Inhibitors).

Toxic Substances (313)

Component	CAS #	Max %	Comments
None		%	

GLOSSARY OF ABBREVIATIONS

ACGIH	American Conference of Governmental Industrial Hygienists
CAS	Chemical Abstracts Service
CERCLA	Comprehensive Environmental Response Compensation and Liability Act
CFR	Code of Federal Regulations
COC	Cleveland Open Cup
DOT	Department of Transportation
EPCRA	Emergency Planning and Community Right-to-Know Act (aka SARA)
IARC	International Agency for Research on Cancer
NIOSH	National Institute for Occupational Safety and Health
NTP	National Toxicology Program
OSHA	Occupational Safety and Health Administration
PEL	Permissible Exposure Limit
RCRA	Resource Conservation and Recovery Act
REC	Recommended
REL	Recommended Exposure Limit
SARA	Superfund Amendments and Reauthorization Act
STEL	Short-Term Exposure Limit
TCLP	Toxicity Characteristics Leaching Procedure
TLV	Threshold Limit Value
TSCA	Toxic Substances Control Act
VOC	Volatile Organic Compounds