



SP-735

Parts Cleaner Concentrate

SP-735 is a liquid cleaning compound and corrosion inhibitor designed for use in high-pressure production spray washers. It is intended primarily for use in the removal of coolants, machining fluids, and honing oils from machined metal surfaces.

SP-735 has broad corrosion-inhibiting characteristics. It will provide corrosion protection to ferrous and non-ferrous metals. In addition to preventing rust on cast iron and steel, it is extremely effective in the prevention of corrosion and staining on aluminum. This makes SP-735 especially suited for use in washing aluminum engine blocks, heads, and aluminum transmission parts and cases. SP-735 also prevents the corrosion of brass and bronze, both on parts and in washer components.

SP-735 is a low-foaming cleaner normally used at concentrations of 3-4%. SP-735 solutions reject oil, leading to enhanced washer cleanliness and extended solution life.

SP-735 solutions are heat stable and will neither break down nor lose corrosion protection properties in washers operated at temperatures as high as 140°F. Use at ambient temperature is recommended in most applications to reduce the formation of

residues through evaporation of water from hot surfaces.

SP-735 responds readily to conventional waste treatment procedures and contains no toxic ingredients or dyes. It is phosphate-free, and contains no silicates or nitrites. It does not contain EDTA, NTA, or related materials and a 0.5% solution shows a chemical oxygen demand of less than 1000 mg/l. It is not corrosive or combustible and requires only normal care in storage, handling, and use (see the MSDS for further information).

TYPICAL PROPERTIES:

Appearance:	Clear liquid
Odor:	Chemical
pH (Concentrate)	10.8
pH (3%)	9.5
Specific Gravity:	1.12
Density:	9.34 pounds/gallon
Foam Character:	Low

AUTOMOTIVE APPROVALS:

DaimlerChrysler NPM Number	12-270-5825
GM (plant specific)	#275 RTO 348704

Rev. 6/05

WARRANTY:

Producto Chemicals will grant credit on any product which proves defective in material or workmanship as determined by us subject to the following conditions: all material is subject to our inspection prior to issuing credit; any refund will be adjusted based on the volume of product used; no credit will be granted for used or unused product(s) over one year old as determined by the batch number; no credit will be granted for product placed or stored in a bulk storage tank, mixed with other material or batches in a bulk storage tank or for any material not in original container. The terms in this warranty do not in any way extend to any product thereof covered by this agreement, which has a life, under normal usage, inherently shorter than the one-year period indicated above. Except as set forth expressly in writing herein, there are no other warranties express or implied in respect of any product.

No warranty of merchantability or fitness for purpose shall apply.

LIMITATION OF LIABILITY:

Under no circumstances shall we or any affiliate of ours have any liability whatsoever for loss of use or for any indirect or consequential damages.



31003 Industrial Road • Livonia, MI 48150
Phone: 734-422-2010 • Fax: 734-422-0244

