



SP-840NK



Parts Cleaner Concentrate

SP-840NK is an alkaline rust-inhibitive cleaning compound designed specifically for use in cleaning machining coolants, drawing compounds, and oils from iron or steel surfaces in high-pressure spray washers. SP-840NK can also be used in dip or soak operations.

SP-840NK is intended for use in high-pressure spray washers operating at ambient or elevated temperatures. SP-840NK is an oil-rejecting cleaner and does not foam. The usual recommended operating concentration for this product is 2-3% in water for removing metalworking fluids. Higher concentrations are sometimes necessary for difficult heavy oils and greases. Concentrations ranging from 5% to 10% are sometimes used in dip or soak tank washers.

SP-840NK also finds use as a corrosion inhibitor. Applied at a concentration of 10-15%, SP-840NK will prevent rust for extended periods of time.

The corrosion-inhibiting residue left on parts washed with SP-840NK will not char or generate smoke when parts are heated. As a result, SP-840NK residues will not interfere with brazing or welding. This makes SP-840NK ideal for washing and/or leak testing

exhaust manifolds and other parts that are subject to becoming hot in use.

SP-840NK responds readily to conventional waste treatment procedures. This product is a corrosive, alkaline material and proper precautions should be taken in handling. As with any chemical, we recommend the wearing of safety glasses and rubber gloves when handling (see the MSDS for further information).

TYPICAL PROPERTIES:

Appearance:	Clear
Odor:	Chemical
pH (Concentrate)	12.5
pH (2.0%)	10.5
Specific Gravity:	1.14
Density:	9.5 pounds/gallon
Foam Character:	Low

AUTOMOTIVE APPROVALS:

Ford Tox Number	170261
-----------------	--------

Rev. 6/05

WARRANTY:

Producto Chemicals will grant credit on any product which proves defective in material or workmanship as determined by us subject to the following conditions: all material is subject to our inspection prior to issuing credit; any refund will be adjusted based on the volume of product used; no credit will be granted for used or unused product(s) over one year old as determined by the batch number; no credit will be granted for product placed or stored in a bulk storage tank, mixed with other material or batches in a bulk storage tank or for any material not in original container. The terms in this warranty do not in any way extend to any product thereof covered by this agreement, which has a life, under normal usage, inherently shorter than the one-year period indicated above. Except as set forth expressly in writing herein, there are no other warranties express or implied in respect of any product.

No warranty of merchantability or fitness for purpose shall apply.

LIMITATION OF LIABILITY:

Under no circumstances shall we or any affiliate of ours have any liability whatsoever for loss of use or for any indirect or consequential damages.



31003 Industrial Road • Livonia, MI 48150
Phone: 734-422-2010 • Fax: 734-422-0244

