



SP-855



Parts Cleaner Concentrate

SP-855 is an alkaline cleaning compound designed specifically for use in cleaning machining coolants, drawing compounds and oils from iron or steel surfaces in spray washers. SP-855 can also be used in dip or soak operations.

SP-855 will not cause pitting, corrosion or staining on rough cast or machined surfaces. SP-855 protects iron and steel from rusting without the addition of supplemental corrosion inhibitors.

SP-855 is intended for use in spray washers operating at ambient or elevated temperatures. The usual recommended operating concentration is 2% to 3% in water for spray operations. Higher concentrations are sometimes necessary for difficult heavy oils and greases. Higher concentrations of SP-855, ranging from 5% to 10%, are sometimes used in dip or soak tank washers.

SP-855 responds readily to conventional waste treatment procedures. This product is an alkaline, corrosive material and proper precautions should be taken in handling. As with any chemical, we recommend the wearing of safety glasses and rubber gloves when handling (see the MSDS for further information).

TYPICAL PROPERTIES:

| | |
|-------------------|-------------------|
| Appearance: | Clear |
| Odor: | Chemical |
| pH (Concentrate) | 12.7 |
| pH (3.0%) | 10.5 |
| Specific Gravity: | 1.15 |
| Density: | 9.6 pounds/gallon |
| Foam Character: | Low |

AUTOMOTIVE APPROVALS:

| | |
|----------------------|-------------|
| Ford Tox Number | 161312 |
| Ford Part Number | 14351594 |
| DaimlerChrysler NPM# | 12-270-5828 |

Rev. 6/05

WARRANTY:

Producto Chemicals will grant credit on any product which proves defective in material or workmanship as determined by us subject to the following conditions: all material is subject to our inspection prior to issuing credit; any refund will be adjusted based on the volume of product used; no credit will be granted for used or unused product(s) over one year old as determined by the batch number; no credit will be granted for product placed or stored in a bulk storage tank, mixed with other material or batches in a bulk storage tank or for any material not in original container. The terms in this warranty do not in any way extend to any product thereof covered by this agreement, which has a life, under normal usage, inherently shorter than the one-year period indicated above. Except as set forth expressly in writing herein, there are no other warranties express or implied in respect of any product.

No warranty of merchantability or fitness for purpose shall apply.

LIMITATION OF LIABILITY:

Under no circumstances shall we or any affiliate of ours have any liability whatsoever for loss of use or for any indirect or consequential damages.



31003 Industrial Road • Livonia, MI 48150
Phone: 734-422-2010 • Fax: 734-422-0244

